

DATASHEET · PUMP HEADS & TUBING

YZ35PPS High-Flow Peristaltic Pump Head.

SKU RBP-0016 Spec v1 Rev. 2026-07-09

DATASHEET · P
RBP-
 Rev 2026
PREVIEW — FIELDS F



PRODUCT FAMILY
 ANIMAL MODEL
 APPLICATION
 COUNTRY OF ORIGIN
 MFG. STANDARD
 LOT TRACEABLE **No**
 VERIFIED **Spec v1 · 2026-07-09**

PRODUCT SPECIFICATIONS

FROM PUBLISHED PROD

MODEL	YZ35PPS	FLOW RATE RANGE	740 - 12,000 mL/min
SPEED RANGE	60 - 600 RPM	NUMBER OF CHANNELS	1
NUMBER OF ROLLERS	3	BODY MATERIAL	PPS (Polyphenylene Sulfide)
ROLLER MATERIAL	Metal	TUBING WALL THICKNESS	3.3 mm
COMPATIBLE TUBING	73# (9.5 mm ID, 6,000 mL/min max), 82# (12.7 mm ID, 12,000 mL/min max)	DIMENSIONS L×W×H (MM)	24.0 × 26.1 × 18.0
WEIGHT (KG)	4.5	AVAILABILITY	In stock

BILL OF MATERIALS · 1 LINE ITEMS

BASE CONF

QTY	ITEM	SKU
1	YZ35PPS High-Flow Peristaltic Pump Head	RBP-0016



Scope.

INFO@CONDUCTSCIENCE.COM CONDUCTSCIENCE.COM

RBP-0016 · DATASH

DATASHEET · PUMP HEADS & TUBING

YZ35PPS High-Flow Peristaltic Pump Head.

SKU RBP-0016 Spec v1 Rev. 2026-07-09

DATASHEET · P

RBP-

Rev 2026

PREVIEW — FIELDS F

BILL OF MATERIALS · EXTENDED ATTRIBUTES

ITEM

YZ35PPS High-Flow Peristaltic Pump Head

MATERIALS REFERENCE

0 MATERIAL

CODE

DESCRIPTION

PROPERTIES

USED IN

Cross-reference.

DATASHEET · PUMP HEADS & TUBING

YZ35PPS High-Flow Peristaltic Pump Head.

SKU RBP-0016 Spec v1 Rev. 2026-07-09

DATASHEET · P

RBP-

Rev 2026

PREVIEW — FIELDS F

OPERATING & STERILIZATION ENVELOPES

CONDITIONS, CYCLES, COMI

OPERATING

TEMPERATURE

HUMIDITY

PRESSURE

STORAGE

TEMPERATURE

HUMIDITY

ORIENTATION

STERILIZATION & CLEANING

AUTOCLAVE

GAMMA

AVOID

ETO

WIPE

ANIMAL COMPATIBILITY

BY SPECIES

NOTES

USE & S

SPECIES

BODY WEIGHT

CHAMBER FIT

Specifications verified against current published product data. Verified 2026-07-09 · Since 2026-07-09.

Cite: ConductScience RBP-0016, Spec v1, 2026-07-09. conductscience.com/lab/high-flow-pump-head

INFO@CONDUCTSCIENCE.COM CONDUCTSCIENCE.COM

RBP-0016 · DATASH